



VISTA NCD/NCL CKe

COMBINATION CAMERA KITS



IDEAL FOR APPLICATIONS SUCH AS:

- Retail environments
- Offices
- Warehouses
- Hotels & reception areas

CAMERA KIT WITH BUILT-IN VARIFOCAL LENS

The Vista NCD/NCL CK Range of 1/3" colour and monochrome camera kits has been designed for entry level applications, without compromising quality of image or features provided.

There are four models in the range, giving high and medium resolution, colour and monochrome options which all incorporate a 4~9mm direct drive (DD) varifocal lens. Selectable automatic gain control (AGC), backlight compensation (BLC).

The integral varifocal lens minimises installation time and gives increased flexibility in the choice of camera location.

Supplied in kit form the camera comes complete with mounting bracket, power supply and BNC connectors to ensure the installation process is made all the more simple.

Despite being extremely cost-effective, no compromise has been made to quality and these cameras come with features that small to medium retail outlets, offices, reception foyers and warehouses can all benefit from by providing outstanding value for money and picture quality.

MAIN FEATURES:

- 1/3" CCD colour/monochrome option
- Comes with built-in 4~9mm DD lens
- Kit comes with 12V DC PSU
- Kit comes with internal camera bracket
- BLC - on/off
- AGC - on/off



THE UK'S PREMIER CCTV BRAND



TECHNICAL SPECIFICATIONS

	NCD635CKe	NCD735CKe	NCL635CKe	NCL735CKe
GENERAL:				
SENSOR	1/3" CCD			
TYPE	Monochrome		Colour	
RESOLUTION (TVL)	380	580	330	480
EFFECTIVE PIXELS	512 x 582	753 x 582	500 x 582	752 x 582
SENSITIVITY	0.05 lux	0.1 lux	0.4 lux	0.8 lux
VIDEO OUTPUT	1.0Vpp, 75 Ohm unbalanced			
SIGNAL TO NOISE RATIO	>50dB (AGC off)	>52dB (AGC off)	>48dB (AGC off)	
WHITE BALANCE				Yes
AGC	On/Off switch			
BLC	On/Off switch (centre weighted)			
GAMMA	0.45			
SYNC. SYSTEM	Internal			
ATW RANGE	2700°K - 9000°K			
POWER:				
SUPPLY	12V DC +15% -10%, less than 200mV ripple			
CONSUMPTION	2.2W	2.5W	3.0W	
PHYSICAL:				
OPERATING TEMP.	-10° to +50°C, less than 80% RH			
CAMERA DIMS. (WxHxD)	56 x 52 x 111mm			
BOXED DIMS. (WxHxD)	250 x 60 x 230mm			
NET WEIGHT	0.224Kg		0.229Kg	
GROSS WEIGHT	1.3Kg			
LENS FOCAL LENGTH	4~9mm with direct drive F1.6-360			
LENS FIELD OF VIEW	H= 31.6° ~ 71.0° / V= 23.6° ~ 51.8°			

ORDERING INFORMATION

NCD635CKe	1/3" monochrome, 380TVL, 0.05 lux, 4~9mm DD lens, F1.6~360, 12V DC
NCD735CKe	1/3" monochrome, 580TVL, 0.1 lux, 4~9mm DD lens, F1.6~360, 12V DC
NCL635CKe	1/3" colour, 330TVL, 0.4 lux, 4~9mm DD lens, F1.6~360, 12V DC
NCL735CKe	1/3" colour, 480TVL, 0.8 lux, 4~9mm DD lens, F1.6~360, 12V DC

DISTRIBUTED BY:

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



VISTA NORBAIN HOUSE, ESKDALE ROAD, WINNERSH TRIANGLE, WOKINGHAM, BERKSHIRE. RG41 5TS
 TELEPHONE: +44 (0) 118 944 0123 FAX: +44 (0) 118 944 0999
 WEBSITE: WWW.VISTA-CCTV.COM