



Video Distribution Amplifiers & Equalizers

EDP-No.: 75102

VDA-8CA

- 1 to 4 Inputs
- 2 to 8 Outputs
- Video Bandwidth: 10 MHz (+/-3 db)
- Signal-to-noise Ratio: >55 db
- Integrated Signal Pre-Amplification (Linear Gain)
- Supply Voltage: 230 VAC / 50 Hz



Specifications:

Distribution configurations	4x 1in/2out; 2x 1in/4out; 1in/6out and 1in/2out; 1in/8out
Video inputs	Up to 4x 1.0 to 2.0 Vp-p, (C)CVS, 75 ohms, BNC
Video outputs	Up to 8x 1.0 to 2.0 Vp-p, (C)CVS, 75 ohms, BNC
Video signal bandwidth	0 - 10 MHz (+/-3 db)
Signal pre-amplification range (linear gain)	-6.0 to +6.0 db stepless adjustable (separate per channel)
Tilt	<= 1 % at 50 Hz
Internal adjustments	4 jumper/channel for the output to the input configuration 1 Potentiometer/channel for the stepless adjustment of the linear gain
Supply voltage	230 VAC / 50 Hz
Power consumption	Approx. 6.0 W
Temperature range	+10°C to +35°C
Housing	Steel metal
Colour	Pantone Coolgrey 1C
Dimensions (HxWxD)	44x216x240 mm
Weight	2.5 kg



Accessories	
EDP No. / Type	Description
76407 VDA/AVU-RMK1	19" Rack kit for 1x VDA-8CA or AVU-8/2AL-2
76408 VDA/AVU-RMK2	19" Rack for 2x VDA-8/4CA or 2x AVU-8/2AL-2

Videor Technical E. Hartig GmbH • Maybachstr. 5 • D-63322 Rödermark
Tel: +49 6074/888-0 • Fax: +49 6074/888-100 • e-mail: info@videortechnical.com •
www.videortechnical.com